



JUL-Z104 张力传感器



■受力方向 Load Direction



■传感器接线图 Sensor wiring diagram




■特点与用途 Features&Applications

- ▶旁压式，安装使用方便
- ▶合金钢材质
- ▶大量程，稳定性好
- ▶适用于起重、水利、煤矿等领域的行业的超载控制和过程显示

技术参数 Technical specifications		
量程	Capacity	0-10/20/50/100/150/200KN
输出灵敏度	Rated output	1.0-2.0mV/V
零点输出	Zero balance	±0.05mV/V
非线性	Non-linearity	0.5%F.S
滞后	Hysteresis	0.5%F.S
重复性	Repeatability	0.3%F.S
输入电阻	Input impedance	350/700Ω
输出电阻	Output impedance	350/700Ω
绝缘电阻	Insulation	≥5000MΩ/100VDC
激励电压	Recommended excitation	5 ~ 15VDC
温度灵敏度漂移	Temp.effect.on output	0.05%F.S./10℃
零点温度漂移	Temp.effect.on zero	0.05%F.S./10℃
温度补偿范围	Compensated temp range	-10 ~ 60℃
工作温度	Operation temp range	-20 ~ 80℃
安全超载	Safe overload	150%
极限超载	Ultimate overload	200%
电缆尺寸	Cable size	Φ5x3000mm

外形尺寸 External Dimension



量程	钢丝直径	A	B	C	D
10KN	Φ6-14	160	76	117	45
20KN	Φ10-18	160	76	117	45
50KN	Φ16-22	160	76	117	45
100-200KN	Φ16-22	260	108	170	68